

## SMK-8904 NVR H.264

1. 4 channel IPCAM connect
2. Support CIF/D1 record resolution
3. BUILD-IN DDNS domain name
4. Free of port forwarding
5. CMS – Applicable to iMac OS

Video compression	H.264
Video format	NTSC/PAL
Video output	VGA
VGA resolution	1280*1024 / 800*600
D1 record frame rate	4 CH*25 (PAL) / 30 (NTSC)fps 720x576
CIF record frame rate	4 CH*25 (PAL) / 30(NTSC)fps 352x288
D1 playback frame rate	4 CH*25 (PAL) / 30 (NTSC)fps
CIF playback frame rate	4 CH*25 (PAL) / 30 (NTSC)fps
Network resolution and frame rate	CIF>10fps for each channel or D1>3fps for each channel
IE/CMS	Support
Motion detect	Support
Record mode	Time/sensor/motion
Mobile	Windows mobile, iphone, android, symbian, blackberry
Audio input	1channel for each IPCAM and 1channel for NVR
Audio output	1channel for each IPCAM and 1channel for NVR
Alarm input	1channel for each IPCAM and 4channel for NVR
Alarm output	1channel for each IPCAM and 1channel for NVR
Hard disk	One 2000G
Mouse	Support
Remoter	Support
PTZ	RS485,1channel for each IPCAM and 1channel for NVR
Network	100M RJ45
DVD-RW	Optional
USB port	Two Host2.0
Power supply	12V 3A

NTSC D1:720\*480 CIF:352\*240

PAL D1:720\*576 CIF:352\*288